

ALUMINUM AMMONIUM SULFATE
****ALUMINUM AMMONIUM SULFATE****
 ALUMINUM AMMONIUM SULFATE
 ALUMINUM AMMONIUM SULFATE

MATERIAL SAFETY DATA SHEET

FISHER SCIENTIFIC
 CHEMICAL DIVISION
 1 REAGENT LANE
 FAIR LAWN NJ 07410
 (201) 796-7100

EMERGENCY CONTACTS
 GASTON L. PILLORI
 (201) 796-7100

DATE: 06/20/86
 PO NBR: N/A
 ACCT: 230920-01
 INDEX: 05-8616-80012
 CAT NO: A567500

THE INFORMATION BELOW IS BELIEVED TO BE ACCURATE AND REPRESENTS THE BEST INFORMATION CURRENTLY AVAILABLE TO US. HOWEVER, WE MAKE NO WARRANTY OF MERCHANTABILITY OR ANY OTHER WARRANTY, EXPRESS OR IMPLIED, WITH RESPECT TO SUCH INFORMATION, AND WE ASSUME NO LIABILITY RESULTING FROM ITS USE. USERS SHOULD MAKE THEIR OWN INVESTIGATIONS TO DETERMINE THE SUITABILITY OF THE INFORMATION FOR THEIR PARTICULAR PURPOSES.

SUBSTANCE IDENTIFICATION

CAS-NUMBER 7784-26-1

SUBSTANCE: **ALUMINUM AMMONIUM SULFATE**

TRADE NAMES/SYNONYMS: NATURAL TSCHERNIGITE; A-567

CHEMICAL FAMILY:
 INORGANIC SALT

MOLECULAR FORMULA: $Al_2(SO_4)_3 \cdot (NH_4)_2 \cdot SO_4 \cdot 24H_2O$ MW: 906.65

CERCLA RATINGS (SCALE 0-3): HEALTH=U FIRE=0 REACTIVITY=0 PERSISTENCE=3

COMPONENTS AND CONTAMINANTS

PERCENT: >97 COMPONENT: ALUMINUM AMMONIUM SULFATE

PERCENT: <3 COMPONENT: ALUMINUM OXIDE

OTHER CONTAMINANTS: NONE

EXPOSURE LIMITS:

2 MG(CAL)/M3 ACGIH TWA

PHYSICAL DATA

DESCRIPTION: WHITE POWDER OR CRYSTALS; ODORLESS

BOILING POINT: 248 F (120 C) MELTING POINT: 202 F (94 C)

SPECIFIC GRAVITY: 1.6 PH: ACIDIC IN SOLUTION SOLUBILITY IN WATER: 15%

SOLVENT SOLUBILITY: DILUTE ACID; INSOLUBLE IN ALCOHOL

Dodecahydrate?

FIRE AND EXPLOSION DATA

FIRE AND EXPLOSION HAZARD:
NEGLEGIBLE FIRE AND NEGLIGIBLE EXPLOSION HAZARD IN DUST FORM WHEN EXPOSED TO HEAT OR FLAME.

FIREFIGHTING MEDIA:
DRY CHEMICAL, CARBON DIOXIDE, WATER SPRAY OR FOAM
(1984 EMERGENCY RESPONSE GUIDEBOOK, DOT P 5800.3).

FOR LARGER FIRES, USE WATER SPRAY, FOG OR ALCOHOL FOAM
(1984 EMERGENCY RESPONSE GUIDEBOOK, DOT P 5800.3).

FIREFIGHTING:
NO ACUTE HAZARD. MOVE CONTAINER FROM FIRE AREA IF POSSIBLE. AVOID BREATHING VAPORS OR DUSTS; KEEP UPWIND.

TOXICITY

CARCINOGEN STATUS: NONE.
ALUMINUM AMMONIUM SULFATE IS AN EYE, SKIN, AND MUCOUS MEMBRANE IRRITANT.

HEALTH EFFECTS AND FIRST AID

INHALATION:
IRRITANT.

ACUTE EXPOSURE- MAY CAUSE IRRITATION WITH COUGHING, CHEST PAIN, AND DYSPNEA.

CHRONIC EXPOSURE- NONE REPORTED IN HUMANS.

FIRST AID- REMOVE FROM EXPOSURE AREA TO FRESH AIR IMMEDIATELY. IF BREATHING HAS STOPPED, PERFORM ARTIFICIAL RESPIRATION. KEEP AFFECTED PERSON WARM AND AT REST. GET MEDICAL ATTENTION.

SKIN CONTACT:
IRRITANT.

ACUTE EXPOSURE- MAY CAUSE MILD IRRITATION.

CHRONIC EXPOSURE- REPEATED OR PROLONGED CONTACT MAY CAUSE DERMATITIS.

FIRST AID- REMOVE CONTAMINATED CLOTHING AND SHOES. WASH AFFECTED AREAS WITH SOAP OR MILD DETERGENT AND LARGE AMOUNTS OF WATER UNTIL NO EVIDENCE OF CHEMICAL REMAINS (APPROXIMATELY 15-20 MINUTES). GET MEDICAL ATTENTION IF NECESSARY.

EYE CONTACT:
IRRITANT.

ACUTE EXPOSURE- DIRECT CONTACT WITH POWDER OR CRYSTALS MAY CAUSE REDNESS OR IRRITATION.

CHRONIC EXPOSURE- MAY CAUSE CONJUNCTIVITIS.

INGESTION:
IRRITANT.

ACUTE EXPOSURE- MAY CAUSE BURNING PAIN IN THE MOUTH AND THROAT, VOMITING, WATERY OR BLOODY DIARRHEA, ANOREXIA, TENESMUS, RETCHING, HEMOLYSIS, HEMATURIA, ANURIA, LIVER DAMAGE AND JAUNDICE, HYPOTENSION, COLLAPSE, AND CONVULSIONS.

FIRST AID- IF VICTIM IS CONSCIOUS, IMMEDIATELY GIVE 2 TO 4 GLASSES OF WATER, AND INDUCE VOMITING BY TOUCHING FINGER TO BACK OF THROAT. GET MEDICAL ATTENTION IMMEDIATELY.

REACTIVITY

REACTIVITY:
STABLE UNDER NORMAL TEMPERATURES AND PRESSURES.

INCOMPATIBILITIES:
SUBSTANCE CAN REACT WITH ALKALINE MATERIALS AND IS SLIGHTLY CORROSIVE TO METALS IF IN SOLUTION.

DECOMPOSITION:
THERMAL DECOMPOSITION MAY RELEASE TOXIC OXIDES OF CARBON, OF NITROGEN, AND OF SULFUR.

POLYMERIZATION:
NOT KNOWN TO OCCUR.

CONDITIONS TO AVOID

AVOID CONTACT WITH ALKALINE MATERIALS AND HEATING TO DECOMPOSITION.

SPILL AND LEAK PROCEDURES

OCCUPATIONAL SPILL:
VENTILATE CONFINED SPACES. SWEEP UP, AVOIDING DISPERSION OF DUST, AND COLLECT IN SUITABLE CONTAINER.

PROTECTIVE EQUIPMENT

VENTILATION:
PROVIDE LOCAL EXHAUST VENTILATION OR GENERAL DILUTION VENTILATION TO MEET PERMISSIBLE EXPOSURE LIMITS.

RESPIRATOR:
200 MG(CAL)/M3- HIGH EFFICIENCY PARTICULATE RESPIRATOR.

FIREFIGHTING- SELF-CONTAINED BREATHING APPARATUS OPERATED IN PRESSURE-DEMAND OR OTHER POSITIVE PRESSURE MODE.

---CLOTHING:

---PROTECTIVE CLOTHING NOT REQUIRED. AVOID REPEATED OR PROLONGED CONTACT WITH THIS SUBSTANCE.

GLOVES:

PROTECTIVE GLOVES ARE NOT REQUIRED BUT RECOMMENDED.

EYE PROTECTION:

EMPLOYEE MUST WEAR SPLASH-PROOF OR DUST-RESISTANT SAFETY GOGGLES TO PREVENT EYE CONTACT WITH THIS SUBSTANCE.

AUTHORIZED - ALLIED FISHER SCIENTIFIC

CREATION DATE: 03/21/85

REVISION DATE: 04/26/85

-ADDITIONAL INFORMATION-

THE INFORMATION BELOW IS BELIEVED TO BE ACCURATE AND REPRESENTS THE BEST INFORMATION CURRENTLY AVAILABLE TO US. HOWEVER, WE MAKE NO WARRANTY OF MERCHANTABILITY OR ANY OTHER WARRANTY, EXPRESS OR IMPLIED, WITH RESPECT TO SUCH INFORMATION, AND WE ASSUME NO LIABILITY RESULTING FROM ITS USE. USERS SHOULD MAKE THEIR OWN INVESTIGATIONS TO DETERMINE THE SUITABILITY OF THE INFORMATION FOR THEIR PARTICULAR PURPOSES.